US006213341B1

(12) **United States Patent**
Keith, III et al.

(10) **Patent No.: US 6,213,341 B1**
(45) **Date of Patent: Apr. 10, 2001**

(54) **SAFE FOR HOLDING AND DISPENSING CHANGE**

(75) Inventors: **Jasper Newton Keith, III**, Lilburn; **William L Gunn**, Atlanta; **W. Chris Morgan**, Blairsville, all of GA (US)

(73) Assignee: **Brink's Incorporated**, Darien, CT (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **09/150,115**

(22) Filed: **Sep. 9, 1998**

(51) **Int. Cl.**[7] **G07F 11/00**

(52) **U.S. Cl.** **221/6**; 221/2; 221/7; 221/14; 221/131; 221/281; 221/270; 700/236; 700/242; 700/244

(58) **Field of Search** ..... 221/2, 6, 7, 11, 221/14, 123, 131, 270, 274, 275, 281, 311, 312 R; 700/236, 242, 244

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,238,725	*	4/1941	Fry	221/270
2,638,396	*	5/1953	Gabrielson	221/6
2,843,242	*	7/1958	Gabrielson et al.	221/274
3,753,507	*	8/1973	James et al.	221/7
4,355,733	*	10/1982	Schoenkopf et al.	221/123
5,207,784	*	5/1993	Schwartzandruber	221/14
5,632,408	*	5/1997	Mitchell	221/131
5,899,358	*	5/1999	Daumueller	221/2
5,938,072	*	8/1999	Lamoureux et al.	221/7

FOREIGN PATENT DOCUMENTS

2237562	*	5/1991	(GB)	221/2
0132590	*	5/1990	(JP)	221/281
0224197	*	9/1990	(JP)	221/281
404102189A	*	4/1992	(JP)	221/6

* cited by examiner

Primary Examiner—H. Grant Skaggs
(74) *Attorney, Agent, or Firm*—Kilpatrick Stockton

(57) **ABSTRACT**

Change dispensing apparatus having multiple columns for storing and vending tubes containing change in coin or in currency. The denominations being vended by a particular machine, the unit value of that denomination, and the value of a tube containing a predetermined quantity of that denomination, are user-programmable for each machine, and any combination of denominations can be user-assigned to the columns. The tube locations in each column are monitored to detect tubes in each column, providing a running indication of the amount of change remaining for each denomination in the safe, and for the total value of change in the safe. An ejector is positionable at the lower end of each column and contains a member for selectably extracting the lowermost tube in each column. The change safe on request prints reports of change usage and other factors associated with the safe, and also predicts the amount of change required for future usage.

18 Claims, 15 Drawing Sheets





FIG. 1


163
153
162
38
77
78
85
23
34
112
82
90
111
28a
80
68
57
52
53
138
123
138a
33a
35
32
28
27
26

FIG. 3



FIG. 2



FIG. 6


132
140
123
127
82
111
112
78
181
179
155
155b
155c
178
174u
90
155b
156
155a
180
174l
92
96
166
155d
170
154
85
177
167
186
97
160
187
98
185
153
153
163
162
38
33
77
80
66

FIG. 4



FIG. 5



FIG. 7



FIG. 9



FIG. 8



FIG. 10


150
177
EJECTOR CARRIAGE POSITION MOTOR
EJECTOR HOME POSITION SENSOR
EJECTOR MOTOR
171
185
EJECTOR CARRIAGE POSITION SENSORS
142
TUBE BLOCKER SWITCH
64
LOWER DOOR SWITCH
140
TUBE BLOCKER SOLENOID
49
UPPER DOOR SWITCH
115
TUBE COLUMN SENSORS
PROCESSOR
59
UPPER DOOR SOL. SWITCH
74
LOWER DOOR SOL. SWITCH
UPPER DOOR SOLENOID
LOWER DOOR SOLENOID
40
TUBE FLAP SWITCH
57
181
72
41, 42
TERMINAL & PRINTER
TOUCH MEMORY PORT
43

FIG. 11


194
OPERATIONS
ORDERING CHANGE (FIG. 20)
320
PRODUCE REPORTS (FIG. 19)
290
AUDIT CONTENTS OF CHANGE SAFE (FIG. 18)
266
TRANSFER TUBES FROM RESERVE TO COLUMNS (FIG. 16)
244
VEND CHANGE FROM CHANGE SAFE (FIG. 17)
255
TRANSFER TUBES FROM DELIVERY (FIG. 15)
DELIVER CHANGE TO CHANGE SAFE (FIG. 14)
195
CONFIGURE CHANGE SAFE (FIG. 13)

FIG. 12


CONFIGURE DENOMINATIONS/ COLUMNS
196
197
200
CHANGE COLUMNS
CHANGE DENOMINATIONS
207
201
ENTER PREPAY REQUIRED
DENOM. FOR COL X:
PENNIES
NICKLES
...
TWENTIES
198
CHANGE DENOM:
PENNES
NICKLES
...
208
ENTER DENOM. IS PAYOUT
202
ENTER NEW DENOM. NAME
209
ENTER SUPERVISOR USE ONLY
REMOVE COLUMNS
203
ENTER NEW UNIT VALUE
210
ENTER TIME DELAY /VEND
199
204
ENTER NEW TUBE VALUE
211
ENTER PAYOUT TIMES
205
ENTER MAX BALANCE
END
206
ENTER MAX TUBES/VEND

FIG. 13


TOUCH ELECTRONIC KEY (43)
216
ENTER CHANGE BAG SEAL NO.
217
ENTER AMOUNT OF DELIVERY
218
UNLOCK LOWER DOOR
219
OPEN LOWER DOOR
PLACE CHANGE IN LOWER COMPARTMENT
220
CLOSE LOWER DOOR
RECEIVE DELIVERY MESSAGE
VERIFY DELIVERY
224
PRINT REPORT

FIG. 14


VEND CHANGE
255
ENTER CASHIER PIN
256
ENTER DENOMINATION TO VEND
257
ENTER NUMBER OF TUBES
257a
ENTER MORE DENOMINATIONS?
257b
259
ERROR MESSAGES?
Y
N
ONLY X TUBES OF (DENOM)
FOR PAYOUT ONLY
INITIATE VEND
FOR SUPERVISOR USE
NOT PERMITTED AT THIS TIME
END

FIG. 17


228
ENTER SUPERVISOR PIN
UNLOCK LOWER DOOR
REMOVE CHANGE FROM DELIVERY
229
CLOSE LOWER DOOR
230
LOAD TUBES INTO COLUMNS?
N
Y
231
(1) APPLY TO DELIVERY ADJUSTMENT
(2) ADD TO RESERVE
(1)
(2)
232
UNLOCK TUBE BLOCKER
OPEN TUBE BLOCKER
LOAD TUBE(S) INTO COLUMNS
236
CLOSE TUBE BLOCKER
232
DISPLAY: DELIVERY TRANSFERED BALANCE
233
IF POSITIVE BALANCE:
(1) LOAD MORE TUBES
(2) ADD TO RESERVE
(3) APPLY TO DELIVERY ADJUSTMENT
(1)
(2)
(3)
235
DENOMINATIONS: AMOUNTS TO ADD- $XX.XX
236
OPEN UPPER DOOR
PLACE CHANGE IN RESERVE
238
CLOSE UPPER DOOR
239
DELIVERY: TRANSFERRED XX.XX BALANCE XX.XX
240
Y
LOAD TUBES INTO COLUMNS?
N
END

FIG. 15


244
TRANSFER CHANGE FROM RESERVES TO COLUMNS
OPEN UPPER DOOR
REMOVE DESIRED AMOUNT FROM UPPER RESERVE
245
CLOSE UPPER DOOR
OPEN TUBE BLOCKER
248
LOAD TUBES
CLOSE TUBE BLOCKER
250
STARTING RESERVE: XX.XX
TRANSFERRED: XX.XX
BALANCE: XX.XX
251

FIG. 16


ORDERING CHANGE
320
325
PREDICTIVE ORDERING OF CHANGE
MANUAL ORDERING
322
326
SET DELIVERY DAYS
CALCULATE ROLLING AVERAGE CHANGE USAGE, BY DAY OF WEEK
PREDICT CHANGE REQUIRED FOR DELIVERY DAY + DAYS UNTIL NEXT DELIVERY
328
ORDER PREDICTED AMOUNT?
330

FIG. 20


266
AUDIT CONTENTS
267
AUDIT TUBE COLUMNS?
Y
N
268
OPEN BLOCKER DOOR
AUDIT COLUMN (DENOM)
269
VEND ALL TUBES IN (DENOM) COLUMN
ENTER AMOUNT VENDED: $XX.XX
RELOAD (DENOM) TUBES INTO COLUMN
272
273
AUDIT NEXT DENOM?
Y
N
274
CLOSE BLOCKER DOOR
275
AUDIT RESERVE?
N
Y
277
OPEN UPPER DOOR
REMOVE CHANGE IN RESERVE
ENTER AMOUNT IN RESERVE: $XX.XX
280
REPLACE IN RESERVE
CLOSE UPPER DOOR
277
AUDIT CHANGE DELIVERY?
N
Y
278
OPEN LOWER DOOR
REMOVE CHANGE DELIVERY
ENTER AMOUNT DELIVERED (DENOMS)
REPLACE CHANGE INTO DELIVERY
CLOSE LOWER DOOR
283
284
PRINT REPORT

FIG. 18


PRODUCE REPORTS
290
REPORT CONFIGURATION OF SAFE
310
DAY REPORT
305
SHIFT REPORT
304
REPORT AVERAGE USAGE
301
REPORT ACTUAL USAGE
300
DENOM; DAY OF WEEK
DISPLAY TUBE LEVELS
291
COLUMN X IS Y TUBES OF (DENOM) VALUE: $ZZZ.ZZ
292
TUBE CONTENTS TOTAL VALUE: $XXX.XX
293
RESERVE: $XXX.XX
294
CHANGE DELIVERED (IF APPLICABLE) :$XXX.XX
295
TOTAL IN CHANGE SAFE: $XXX.XX
296

FIG. 19

SAFE FOR HOLDING AND DISPENSING CHANGE

FIELD OF THE INVENTION

This invention relates in general to safes, and relates in particular to safes for receiving supplies of change and dispensing predetermined amounts of that change on request.

BACKGROUND OF THE INVENTION

Cashiers and clerks at retail sales locations need a ready and convenient supply of change on hand at all times. "Change" as used herein is not limited to coins, but also includes bills of denominations sufficient to meet change-making requirements for the particular business. Failure to maintain adequate change at a cash register or the cash drawer of a point-of-sale terminal may at times delay completing retail transactions while the cashier obtains a new supply of change, a practice which may reduce the total volume of sales and irritate customers who must wait while the cashier or a supervisor delivers change from a locked safe or some other secure location.

The requirement for maintaining an adequate and convenient supply of change is particularly important in certain kinds of retail sales locations such as convenience stores and gas stations, where the amount of each transaction may be relatively low and cash frequently is tendered to pay the transaction. Moreover, some suppliers of merchandise for convenience stores traditionally require payment in cash on delivery of the merchandise, and those cash payments will further deplete the amount of money remaining in the cash register or point-of-sale terminal drawer for making change.

Safes intended for storing and dispensing change are known in the prior art. Such safes heretofore have been relatively complex in construction and may lack the flexibility of storing and dispensing change of varying amounts and capacities. Moreover, such change-holding safes of the prior art lack the accounting and audit capabilities desirable to identify amounts of change dispensed and to audit the amounts remaining in the safes. Such known change dispensing safes also lack provisions for temporarily storing and accounting for deliveries of change by an armored-car messenger or other service, so that the change is at hand but remains secured within the safe itself.

SUMMARY OF THE INVENTION

Stated in general terms, a change safe according to the present invention has a plurality of columns, each column receiving several units of change so that each unit occupies a predetermined location in the column. The change safe detects the level of units in each column, so that the amount of change in each available denomination is always known. The actual change, whether a predetermined number of wrapped coins or of paper currency, preferably is loaded in cylindrical tubes of predetermined configuration, so that the dispensing mechanism and sensing elements always act on articles of the same predetermined size and shape. The present apparatus on demand vends individual units that contain selected variable amounts of coin or currency so that each tube in each column contains a known amount of change. The denominations of coin or currency in the tubes loaded into each column and dispensed from those columns, and various parameters relating to permitted vending operation for each denomination, are selectable by the user of the safe, providing flexibility for conforming the use of the present safe to the needs of different locations in which the safe is used.

Stated somewhat more particularly, sensors are associated with each column detect the tubes at the predetermined locations in the columns. Those sensors determine at all times the number of tubes remaining in the safe for dispensing. In the disclosed embodiment of the safe, tubes are dispensed from the lowermost location of each column, and the tube-dispensing mechanism is selectively operable to determine whether an article is present at that location, so that no article-detecting sensor is required for the lowermost location in each column.

Stated in somewhat more detail, the article dispensing mechanism includes an element moveable in a first direction to withdraw the lowermost article from a selected column, thereby dispensing that article from the safe. However, that displacement element is selectably operative to move in a second direction which engages the lowermost article and attempts to displace that article in a direction along which movement is blocked. If an article is present in the lowermost location, that blocked movement of the displacement element in the second direction is detected so that the displacement element indicates the presence of an article at that location. However, if the displacement element moves in the second direction without hindrance, that movement indicates the absence of an article at the lowermost location, corresponding to a condition in which the particular column contains no article to be dispensed.

The article dispensing apparatus includes a displacement element moveable on an orbital path that includes the position occupied by the lowermost article present in a selected column. However, the lowermost article is moveable from that position only in a first direction of movement of the displacement element, namely, the direction to dispense that article from the column. When the displacement element is operated to move in the opposite direction along the orbital path, the lowermost article (if present) prevents the displacement element from completing that commanded movement, and that blocked movement is detected to indicate that an article is present at the lowermost location of the particular column.

The moveable displacement element is mounted on a carriage that traverses to juxtapose the displacement element with the lowermost location of each selected column in the change-dispensing apparatus. The apparatus responds to a request for change of a particular denomination by traversing the carriage as necessary to align the displacement element with a column holding at least one tube containing change of that denomination, and then operates the displacement element to dispense the selected number of articles from that particular column, whereupon the cashier or other person using the apparatus can retrieve the dispensed tube. A sensor detects the presence of each article being dispensed, to verify the act of dispensing an actual physical article in response to the dispensing command.

Tubes are loaded into the columns through separate loading ports at the upper ends of the columns. The loading ports normally are closed by an element that blocks access to the columns, except when change-holding tubes are being loaded into the columns. The control mechanism associated with the change safe selectively unlocks the blocker door, allowing an operator to shift that blocker door to a position opening the ports for loading tubes into the columns. The position of the blocker door is sensed, so that the control mechanism associated with the change safe can provide appropriate operator prompts to close that door after loading a supply of the tubes into one or more columns.

The upper end of each column preferably includes apparatus that prevents each newly-inserted tube from dropping

into the column until that tube is completely inserted through the loading port into the column. This arrangement prevents newly-inserted tubes from descending nose-first into a column, which might jam a subsequent dispensing effort and would produce a false indication of the quantity of tubes loaded into the column. The lower end of each column preferably has a joggle or similar provision for contacting the first tube dropped into an empty column, so as to break the fall of that tube and prevent the falling tube from bouncing out of position when hitting the bottom of the column.

The change dispensing safe according to the present invention also permits selective programming of each column for the denomination of change to be dispensed, and other column-specific variables such as time-of-day use restrictions, maximum number of tubes permitted per dispensing operation, whether prepayment is required from a cash drawer before dispensing change is permitted, and the like. The present safe also monitors patterns of change usage, and uses the information so obtained to forecast amounts of change required for deliveries of change at various times to the particular change safe.

The present safe also includes a separate lockable compartment intended for receiving deliveries of change from an outside source such as an armored-car service or the like. Access to that separate compartment may be limited to supervisory personnel by requiring a particular access code. The operation of the present safe also permits removing quantities of coins from the separate compartment either for loading into the individual change-dispensing columns or into a reserve location within the main compartment of the safe.

Accordingly, it is an object of the present invention to provide an improved apparatus and method for receiving and dispensing change.

It is another object of the invention to provide a change-dispensing apparatus and method offering improved flexibility of operation.

It is a further object of the present invention to provide a change-dispensing apparatus and method in which the denominations of change and other parameters for individual change-vending column areas are selectably and individually programmable by the user of the apparatus.

It is a further object of the present invention to provide a change safe intended for use with a secure depository such as a drop safe used for temporary storage of currency at retail outlets or the like.

Other objects and advantages of the present invention will become more readily apparent from the following description of a preferred embodiment.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a pictorial view of a change safe according to a preferred embodiment of the invention.

FIG. **2** is a semischematic pictorial view of the change safe shown in FIG. **1**, with the upper door open for illustrative purposes.

FIG. **3** is an exploded pictorial view of the change safe shown in FIG. **1**.

FIG. **4** is a partially-sectioned side elevation view of the change safe shown in FIG. **1**.

FIG. **5** is a front elevation view, partially-sectioned and broken away, showing details of the upper-door lock mechanism, the blocker door for loading tubes into the columns, and other details of the change safe shown in FIG. **1**.

FIG. **6** is a detailed view showing the interior of the lower door in the change safe of FIG. **1**.

FIG. **7** is a pictorial view showing rear details of the upper and lower doors, the change dispensing subassembly, and related structure of the change safe shown in FIG. **1**.

FIG. **8** is a detailed pictorial view showing the lower end of several columns for holding tubes of change in the change safe of FIG. **1**.

FIG. **9** is a detailed pictorial view showing the upper end of several such columns including the tube flaps.

FIG. **10** shows a typical tube flap in relation to the wall of a tube column.

FIG. **11** is a block diagram of control apparatus for the disclosed embodiment.

FIG. **12** is flow charts showing operation of the disclosed embodiment.

FIG. **13** is a flow chart showing configuration of the disclosed embodiment for various denominations.

FIG. **14** is a flow chart showing delivery of change according to the preferred embodiment.

FIG. **15** is a flow chart showing handling of delivered change according to the preferred embodiment.

FIG. **16** is a flow chart showing transfer of change from the upper reserve to the columns according to the preferred embodiment.

FIG. **17** is a flow chart showing a typical vending operation according to the preferred embodiment.

FIG. **18** is a flow chart showing audit functions according to the preferred embodiment.

FIG. **19** is a flow chart showing typical audit report functions according to the preferred embodiment.

FIG. **20** is a flow chart showing predictive ordering of change according to the preferred embodiment.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT

FIGS. **1** and **2** show generally at **20** a safe for holding and dispensing change according to a preferred embodiment of the present invention. The safe **20** is defined in part by side walls **21**, a top panel **22**, a bottom panel **23** (FIG. **3**), and a back panel **24** assembled to define the generally boxed-shaped safe **20**. The various panels comprising the outer perimeter of the safe **20** preferably are made of steel or another metal of strength and construction sufficient to withstand at least moderate attempts to force open the change safe.

The front of the safe includes an upper door **26** hinged along the bottom to open by swinging outwardly, as shown in FIG. **2**. A knob **27** is located on the exterior of the upper door **26** and is connected to actuate a bolt mechanism within the safe, as described below. A number of separate ports **28** are horizontally aligned near the upper edge of the door **26**, for selectively loading change holders into corresponding receptacles within the safe. The ports **28** are selectively blocked or unblocked in unison by a slideable blocker plate located behind the upper door **26** and manipulated by the handle **29** extending through a slot to the left of the ports. As explained below, the blocker associated with the ports **28** normally is locked in the closed position by apparatus within the change safe, preventing anyone from tampering with the safe through the ports.

The change safe **20** also has a lower door **32** mounted in a panel **33** located below the upper door **26**. The lower door **32** swings open along a hinge at the left side of that door,

providing access to a lower storage compartment **34** (FIG. **3**) within the change safe. A knob **35** on the lower door **32** actuates an internal locking mechanism for that door, as described below.

The exit of change delivery chute **38** is located on the front panel **33** between the lower door **32** and the bottom of the upper door **26**. Tubes or other articles dispensed from within the change safe drop by gravity to the outer end of the chute **38**, where a cashier or other person may retrieve the articles for use.

The various mechanical and functional operations of the present change safe are controlled by a programmable microprocessor **40**, as is described below in greater detail. That processor is associated with a control terminal **41** for entering commands into the safe and displaying messages, and with a printer **42** for printing various reports relating to the operation and contents of the change safe. In a preferred application of the present change safe, that safe is intended for installation and operation in conjunction with a drop safe of a kind disclosed in U.S. Pat. No. 5,695,038, the disclosure of which is incorporated herein by this reference thereto. That drop safe operates under programmed control, and incorporates a data terminal and a printer, and the change safe described herein preferably is connected to the control processor of the drop safe and shares the microprocessor, the data terminal, and the printer associated with the drop safe. It should thus be understood that the control terminal **41** and printer **42** described herein may advantageously be associated with a drop safe as referenced herein, so that only a single data terminal, printer, and programmed processor are required to operate the present change safe and the drop safe as described in U.S. Pat. No. 5,695,038. This common control of both the drop safe and the change safe afford several operational advantages as described below. Of course, it should be apparent to those skilled in the art that the present change safe may alternatively be operated as a free-standing unit equipped with its own control processor, data terminal, and printer, to operate as described herein independently of any other apparatus.

FIGS. **2**, **3**, and **7** show interior views of the change safe **20**. The upper door **26** is mounted on supports **45** having lower ends pivotally connected at **46** to suitable structure on the inside of the safe **20**. Tension springs **47** attach between the supports **45** and the side walls **21** of the safe to exert a counterbalancing force urging the upper door **26** closed, and buffer cylinders **48** extend in parallel with the springs to inhibit abrupt movement of the upper door when opening or closing that door. The springs **47** and buffers **48** help overcome the significant combined weight of the upper door and the change dispensing subassembly **82** (including coins loaded therein) carried by that door, thereby reducing the risk of personal injury resulting from sudden or uncontrolled movement when the upper door is unlocked.

A switch **49** (FIG. **7**) is mounted adjacent one of the supports **45** for the upper door **26**. The switch **49** changes state whenever the upper door is moved from its fully-closed position as illustrated in FIG. **1** and sends that status to the microprocessor **40**.

The upper door **26** is locked in the closed position by a pair of bolts **52** mounted on the inside of the upper door, each having an inner end connected to the lock cam **53**. The outer ends of the bolts **52** are slideably mounted in openings at the sides **54** of the upper door. The lock cam **53** connects to a cam shaft (not shown) extending through the upper door **26** and connecting to the knob **27** on the front of the upper door. Rotating the knob **27** in either direction thus turns the lock cam **53** through a degree of rotation selectively extending the bolts **52** into mating recesses supported by side walls **21** of the safe on either side of the upper door **26**, or withdraws the bolts from those recesses.

Rotation of the lock cam **53** is selectably blocked or enabled by the upper-door solenoid **57**, having a spring-biased plunger that engages a mating recess in the lock cam **53** when the bolts **52** are extended to lock the upper door. The knob **27** thus cannot turn the lock cam **53** to withdraw the bolts and unlock the upper door unless the upper-door solenoid **57** is energized to withdraw the locking plunger from the lock cam **53**. A switch **59** is mounted adjacent the upper-door solenoid **57** to detect movement of the solenoid plunger to the unlocked position, so that the switch indicates when the upper-door locking mechanism is enabled to unlock that door whether or not the knob **27** has been manipulated to draw the bolts **52**.

The lower door **32** is connected to the change safe by a hinge **62** along the left side of the door. As best seen in FIG. **7**, an arm **63** connects to the inside of the lower door and actuates the lower-door switch **64** mounted on the inside of the front panel **33**. The lower-door switch **64** indicates whether or not the lower door is fully closed.

The locking mechanism for the lower door **32** includes a locking cam **66** on the inside of the lower door, connected by a shaft (not shown) to the knob **35** on the front of that door. The locking cam **66** is mounted in spaced-apart relation to the back of the lower door, and that locking cam includes a cut-away portion **67** providing clearance for the plate **68**, FIG. **3**, immediately behind the front panel portion **33***a* at the right of the lower door. When the lower door **32** is closed, the plate **68** is positioned between the back side of the lower door and the portion **69** of the lock cam **66** that is not cut away. Rotating the lock cam **66** with the lower door closed, thus positions that portion of the lock cam **66** behind the plate **68**, thereby locking the lower door closed.

A lower-door solenoid **72** is mounted on the back of the lower door **32** and has a spring-loaded plunger urged against the periphery of the lock cam **66**. That solenoid plunger engages a notch on the periphery of the lock cam **66** when the lock cam is positioned to lock the lower door, so that the lower door remains locked unless the lower-door solenoid **72** is energized. A switch **74** is mounted to sense the position of the plunger for the lower-door solenoid **72**, so that the switch indicates an unlocked condition of the lower door whether or not that door is open.

The lower door **32** opens to access the lower compartment **34** within the change safe. This lower compartment is available for short-term storage of change delivered by an armored-car service, for example, before accounting for the change within the change safe and adding that change to the dispensing columns or to the reserve location **78** (FIGS. **2** and **3**) located in an upper portion of the change safe, behind the upper door **26**. The lock mechanism for the lower door **32** preferably is enclosed within a housing **80** mounted on the inside of the lower door, to protect that mechanism from contacting bags of change or other items placed within the lower compartment **34**.

A change dispensing subassembly indicated generally at **82** is mounted on the inside of the upper door **26** and moves outwardly with the upper door as that door is opened. The change dispensing subassembly includes a plurality of adjacent spaced-apart vertical partitions **84** defining vertical columns **83**, with the upper end of each column being juxtaposed with corresponding ones of the loading ports **28** formed in the upper door **26**. The dispensing subassembly **82**

also includes an article ejector subassembly **85** mounted below the array of columns **83**, and selectably operative to eject a change tube or other article from any selected column. These two subassemblies are described below.

The partitions **84** defining the columns **83** extend upwardly from lower ends adjoining the substantially horizontal surface **89** of a plate **90** extending beneath the partitions. The horizontal portion **89** of the plate forms the bottom **92** of each column **83** and supports the tube at the lowermost position of each column. A slot **93** is formed in each bottom **92** and extends substantially the entire front-back dimension of the bottom. These slots accommodate the ejector member of the ejector subassembly **85**, as described below.

The plate **90** includes a downwardly-bent portion **96** extending rearwardly from the slotted bottom surface **92**. That downwardly-bent portion in turn leads to a substantially vertical portion that extends around the back of the traversable ejector assembly **85** as best seen in FIG. **4** and ends a short distance above the inner end **98** of the dispensing chute **38**. As will be seen, tubes dispensed rearwardly from the columns **83** fall along the portion **96** of the plate **90** to land on the inner end **98** of the dispensing chute **38**, from which those tubes descend by gravity to the exit end of the chute.

As mentioned above, the preferred embodiment of the present change safe stores and dispenses change contained in cylindrical tubes **102** of predetermined length and diameter. Each such tube typically contains a conventional roll of coins or rolled-up paper money of predetermined denomination and total value. The tubes preferably are made of a rigid material such as plastic or the like, which maintains the predetermined shape of tubes during a vending operation. (It should be understood that items other than money may be contained in the tubes and dispensed by the present apparatus.)

One such tube **102** is shown at FIG. **8** located at the bottom of a column **83**. The view in that figure is taken from the back of the change dispensing subassembly **82**, showing the flat end **103** of the tube **102**. The closure at the opposite end of the tube is inset from that end, so that the circumference of the tube forms an annular ring at that opposite end.

The adjacent partitions **84** forming each column **83** are mutually spaced apart a distance slightly greater than the diameter of the tubes **102**, so that the tubes will readily fall by gravity when inserted into the upper ends of the columns as described below. Each partition near its lower end is bent to form a joggle **106**, with the joggles having approximately the shape of a broad sideways-V extending from the front to the back of each partition. As best seen in FIG. **8**, the peak **107** of the joggle **106** in each partition faces, in spaced-apart complementary fashion, the valley **108** of the joggle in the adjacent partition. These peaks and valleys are spaced above the bottom surface **92** of each column **83** approximately one-half the diameter of the tubes **102**, although that exact spacing is not considered critical. The confronting peak **107** and valley **108** of the joggles in each column locate the lowermost tube **102** in predetermined position on the bottom surface **92**, with the lower side of the horizontal cylindrical tube resting on the slot **93** in the bottom surface of that column. Furthermore, the joggles **106** intercept and break the fall of the first tube **102** dropped into an empty column **83**, reducing the velocity of the tube just before striking the bottom surface **92** of the column and thus reducing the likelihood that the lowermost tube will bounce when dropped onto the bottom surface and become improperly located, leading to problems in a subsequent vending operation.

The columns **83** are further defined by the front plate **111** and back plate **112**, best seen in FIGS. **4** and **9**. The back plate **112** supports a sensor board assembly having vertical arrays of photosensors **115** mounted on the back plate **112** in alignment with the columns **83** between the back and front plates. Each photosensor **115** on the back plate **112** is aligned with the predetermined vertical location of a tube **102** loaded into the columns. The presence of a tube **102** at a particular vertical location, e.g., three tubes up from the bottom of the column, thus is positively detected by the sensor **115** at that particular vertical location in the particular column. This arrangement provides a rapid inventory of the physical contents in each column **83** of the change safe.

Because the ejector subassembly **85** traverses the lowermost locations of the columns **83**, it is not practical to include a photosensor for those lowermost locations. Thus, the number of photosensors **115** mounted for each column on the back plate is one less than the total capacity for tubes in each column. In an actual embodiment of the present change safe, each column holds a maximum of ten tubes and the columns thus each have nine photosensors **115** on the back plate **112**.

The presence of a tube **102** at the lowermost location in a column is implied if the photosensor for at least the next vertical location in that column detects a tube. However, a positive check for a lowermost tube in each column also is available as disclosed below.

Tube flaps shown generally at **123** in FIGS. **9** and **10** are positioned at the upper end of each column **83** in substantially horizontal alignment with corresponding ports **28** in the front of the safe **20**. Each tube flap **123** is engaged when a tube **102** is first inserted into a port **28** and an aligned port **28*a*** in the front plate **111**, and the tube flap **123** prevents a tube from dropping into the corresponding column **83** until the tube is substantially completely inserted through the port.

Each tube flap **123** extends generally from front to back at the top of a corresponding column and is mounted for pivoting movement on a horizontal axis **131**. The tube flaps **123** each have a floor plate **124** whose lower edge **125** overlaps and extends slightly below the upper edge **126** of the partition **84** defining one side of the column. The opposite edge of the floor plate **124** joins an upper plate **127** along a bend line **128** extending the length of the tube flap. The bend line **128** is located a short distance beyond the horizontal axis **131** of rotation, on which the tube flap **123** is mounted within the change dispensing subassembly **82**.

A guide tab **132** extends outwardly and forwardly from the front edge of the upper plate **127**. The guide tab **132** of each tube flap **123** is positioned immediately behind the corresponding tube-loading port **28**, so that the flat end **103** of a tube immediately contacts the guide tab as the tube is initially inserted through the port. That contact with the guide tab causes the tube flap **123** to rotate counterclockwise (as seen in FIG. **9** on the axis **131**, thereby raising the floor plate **124** to partially block the upper end of the column **83**. Continued insertion of the tube **102** through the port **28** slides that tube across the floor plate **124**, so that the tube flap **123** temporarily supports the tube. Once the tube **102** is completely inserted through the loading port **28*a*** so that the trailing end of the tube moves past the edge of the loading port, the tube flap **123** is free to pivot downwardly about the axis **131** to the initial position shown in FIG. **9**

wherein the floor plate **124** returns to engage the upper edge **126** of the partition **84**. That pivoting movement removes the floor plate **124** from its temporary position blocking the upper end of the column **83**, allowing the just-inserted tube **102** to drop within the column until that tube contacts the lowermost end of the column or the last tube previously loaded into the column. In either case, the just-inserted tube cannot fall within the column until substantially fully inserted into the column, thereby preventing the tube from falling head-first into the column after the tube is only partially inserted through the loading port **28**.

As previously mentioned, the tube loading ports **28** are selectably closed by a blocker door to prevent unauthorized access to the columns **83**. This blocking is accomplished by the tube blocker **138** (FIGS. **3** and **5**) in the form of a horizontal plate extending immediately behind the ports **28** through the upper door **26** of the safe. The actuating handle **29** (FIG. **1**) extends forwardly from one end of the tube blocker **38** and projects through the elongated slot in the top door, for manual manipulation of the tube blocker. The tube blocker has an array of ports **138***a* conforming in size and number to the ports **28** in the upper door, and the blocker ports **138***a* either are coaxial with the door ports **28** or are laterally offset to obstruct the door ports, depending on the longitudinal position to which the tube blocker **138** is moved.

A solenoid **140** (FIG. **4**) is located in relation to the tube blocker **138** so that the spring-biased armature of the solenoid engages and locks the tube blocker in position blocking the ports **28** through the upper door of the change safe. The tube blocker **138** is enabled for sliding movement, in response to the handle **29**, only when the solenoid **140** is operated. A switch **142** is located adjacent the tube blocker **138** to detect the open vs. closed position of the tube blocker.

The change ejector subassembly **85** is best understood with regard to FIGS. **4**, **5**, and **7** That subassembly is mounted beneath the change dispensing subassembly **82** for selective positioning beneath any column **83** and operates to eject the lowermost tube **102** from that selected column. The carriage **146** is supported by a threaded horizontal lead screw **147** and a parallel, smooth rod **148** extending horizontally beneath the change dispensing subassembly **82**. A lead screw drive mechanism including a stepper motor **150** is located at one end of the lead screw **147** and selectably rotates the lead screw in either direction. The lead screw **147** engages a nut or the like associated with the carriage **146**, so that the carriage is traversed in either direction along the lead screw and the rod **148** depending on the rotational direction of the rotor **150**.

The carriage **146** has at one side an extractor plate **153** (FIGS. **3** and **4**) that in part defines the path of movement of the extractor **154**, which engages and removes a change tube **102** from the lowermost location in a selected column **83**. The extractor **154**, shown in detail in FIG. **4**, is somewhat Y-shaped and has an extractor finger **155** protruding upwardly from an outer end of a first arm **156** which extends from the central body portion **157** of the extractor. A second arm **160** extends downwardly from the central body portion **157** to an outer end **161**, from which extends a transverse pin **162** slideably engaged in the curved slot **163** formed near the lower edge of the extractor plate **153**.

A third arm **166** of the extractor **154** extends forwardly and upwardly from the central body portion **157** in a somewhat-symmetric relation to the second arm **160**. A roller pin **167** is rotatably attached near one end of the second arm **166** and attaches to the wheel **170** mounted in the carriage **146** parallel to the extractor plate **153**. An ejector stepper motor **171** mounted with the carriage **146** is coupled to the wheel **170** and selectably rotates that wheel in either direction.

The geometry of the extractor **154**, constrained in movement by the pin **162** traveling in the slot **163** of the extractor plate **153**, and by the circular path of the roller pin **167** connected to the wheel **170**, constrains the extractor finger **155** to traverse a closed path somewhat resembling a horizontally-elongated O. The path is parallel to the slot **93** at the bottom **92** of the column **83** beneath which the carriage **146** is positioned. The path **174** has an upper portion **174***u* extending through the slot **93** into the lowermost tube position within that column, and a parallel lower portion **174***l* extending a distance below that slot and thus out of the lower-most tube position within the column.

Movement of the extractor **154** starts from a home position wherein the second arm **160** of the extractor is at its maximum leftward position and the extractor finger **155** is at the position **155***a* near the bottom-left end of the lower portion **174***l* of the traverse path. This home position of the extractor **154** is detected by the sensor **177**, mounted for actuation by the extractor in that home position. Assuming the stepper motor **171** drives the wheel **170** in the clockwise position as viewed in FIG. **4**, the wheel begins raising the outer end of the third arm **166** while simultaneously moving the second arm **160** to the right along the slot **163**. Because the slot curves upwardly from its leftmost end, these movements elevate the first arm **156** and raise the extractor finger along the path **174** to a position **155***b*, in which the extractor finger is positioned to enter the front end of the slot **93** and engage the front end of a tube **102** in the lowermost position of the column. Continued clockwise rotation of the wheel **170** moves the finger **155** along the upper path **174***u*, traversing the finger through the slot **93** and extracting the lowermost tube **102** from the column. This rearward extractive movement of the finger **155** continues until the finger reaches its rearmost position **155***c*, at which time the tube **102** has been fully extracted from the column to drop downwardly along the plate **90** and enter the chute **38** leading to the front of the change safe.

As the finger **155** extracts the tube **102** from the column, that tube encounters and displaces the tube ejection flap **178** extending across the back of the change dispensing subassembly **82** to lie immediately behind the lowermost ends of the columns **83**. The tube ejection flap **178** is pivotably mounted along a horizontal hinge **179** and has an arm **180** operatively associated with a sensor **181** mounted on the change dispensing subassembly **182**. The sensor **181** thus detects the actual physical ejection of a tube from any column **83**, in response to a commanded extraction operation of the extractor **154**.

After the extractor finger **155** reaches the position **155***c*, continued rotation of the wheel **170** draws that finger downwardly to a lower position **155***d*, beneath the rearmost position **155***c* and below the slot **93** at the lowermost end of the column. The finger **155** then moves rearwardly along the lower path **174***l* as the wheel **170** continues to rotate, until the extractor **154** arrives at the home position as determined by the sensor **177**. Sensing the home position signals the microprocessor **40** to stop the ejector stepper motor **171**, completing the cycle for extraction from a column, unless the operator had requested more than one tube from that column.

To provide a positive check for the presence of a tube at the lowermost location in a column, the ejector stepper

motor **171** is operated in a direction opposite to the direction described above to eject a tube from the column. This opposite-direction motion moves the finger **155** in the opposite direction along the path **174** until the finger enters the backend of the slot **93**. If a tube **102** is in the lowermost position of the column, the finger **155** engages the backend of that tube and attempts to move the tube forwardly, but the front plate **111** blocks that attempted forward movement. That blocked movement in the opposite direction thus indicates the presence of a tube at the lowermost location. However, if the finger **155** moves forwardly through the lowermost location without hindrance, that movement indicates the absence of a tube at the lowermost location.

A horizontal array of sensors **185** determines the proper location of the carriage **146** with respect to the columns **83** of the change dispensing subassembly. The sensors **185** are arrayed on a board **186** mounted in front of the moveable carriage, as best shown in FIGS. **4** and **7**. An element **187** is mounted on the carriage **146** for movement therewith along a horizontal path intersecting each sensor **185**, as the motor **150** traverses the carriage beneath the columns. The fixed sensors **185** and the moveable element **187** are positioned relative to the columns so that the sensor associated with a particular column detects the element when the carriage is positioned with the extractor **154** beneath the slot **93** for that column, signaling the microprocessor **40** to stop the carriage at that location.

The change safe preferably operates under programmed control to define denominations of change dispensed by a particular safe, varying levels of access to the safe for dispensing change, for opening the upper and lower doors to receive deliveries of change and to deposit that change into the columns of the safe, and selected other parameters. This system includes the programmable microprocessor **40**, FIG. **11**, programmed to function as a central processing unit (CPU) for the system. The processor includes suitable memory and other elements typically associated with such units, and is connected to receive signals from the various switches and sensors, and to deliver operating signals through appropriate drivers to the solenoids and other actuators, as disclosed herein. As mentioned above, the processor **40** may be physically located in a separate drop safe connected via a signal path to the present change safe.

In addition to the terminal and printer associated with the microprocessor, a portable microchip memory module preferably is used to input information for accessing the lower compartment of the change safe by a messenger delivering a new supply of change. For that purpose, a touch memory port **43** is connected to the microprocessor. That port interfaces with a memory module chip (not shown) carried by the armored-car messenger. Further details of such memory modules are found in the aforementioned U.S. Pat. No. 5,695,038.

Operation of the preferred embodiment is now discussed with reference to the operating menu shown in FIG. **12**. Each submenu in that figure shows a principal operational feature of the change safe, and it will be understood that the microprocessor **40** is programmed to deliver appropriate operating signals and to compile and display information on the printer **42** or on a visual display associated with the terminal **41**. Such programming of microprocessors is well within the skill of the art and need not be detailed herein.

A change safe according to the present invention has multiple columns **83** for receiving change, and any possible combination of certain variables can be assigned to each column. These variables for each column include the denomination of a particular unit of change (e.g., pennies, nickels, or bills such as tens or twenties) for that column, the value of each tube containing that denomination of change (e.g., pennies are $0.50 per tube) the maximum balance to maintain in the change safe for that denomination, the maximum number of tubes for that denomination to be vended at one time, whether the cashier must prepay (e.g., by inserting at least an equal value of bills in a related drop safe) to cover the change vend, whether the denomination may be vended as a cash payout (e.g., paying a vendor for C.O.D. purchases, lottery payouts, refunding customer money), whether only a supervisor may vend this denomination, the amount of time (if any) which must elapse before another vend of this denomination may be made, and any time-of-day restriction to vending the specified denomination.

Selecting principal operations of the change safe is initiated at block **194** in FIG. **12**. Configuring the change safe normally requires approval of a supervisor in the location where the safe is installed, and those skilled in the art will understand that the operation block **194** includes various introductory steps such as requiring entry at the terminal **41** of a proper Personal Identification Number (PIN) for a supervisor. Once the supervisor's pin is entered, the supervisor can elect to configure the change safe as shown in block **195** and as detailed in FIG. **13**. Turning to that figure, the setup routine allows configuring either the individual columns of the change safe as shown at step **197** or the denominations intended for those columns, as shown at step **196**. A new change safe according to the present invention may have all columns set to an unused status, and a display or printed report at that time will indicate "unused" as the denomination for each column. This allows a store supervisors to set up the columns in a way that best fits the operation of a particular store. A typical configuration might be:

Column	Denomination
1	Pennies
2	Pennies
3	Pennies
4	Nickels
5	Nickels
6	Nickels
7	Dimes
8	Quarters
9	Ones
10	Fives

This step is indicated at **198** in FIG. **13**. If the supervisor desires to leave a particular column unassigned or to deselect a column previously assigned a particular denomination, that step is shown at **199** in FIG. **13**. After assigning each available column of the change safe a particular denomination, the supervisor may return to the main menu to select other operations, as indicated by the "End" block in FIG. **13**.

Configuring the change safe to identify possible denominations of change for vending, and to set the various attributes available for each denomination, is shown in FIG. **13** starting with the block **200**. The supervisor may elect to change any denomination previously selected for the change safe, as shown at step **201**. Changing denominations can include adding a new denomination, changing an existing denomination, or simply deleting an existing denomination without substituting a new one. The name of each new

denomination is entered at **202**, after the supervisor selects whether this denomination is new or a change of a previous one. If a new denomination, the supervisor enters its name in the terminal **41**. Next, the new unit value of that denomination is entered as shown at **203**. If the denomination is nickels, the unit value is $0.05; the unit value of a column being set to vend "20s" is $20.00. The cashier then enters the total value of each tube containing that denomination, as indicated at **204**.

After entering the basic information for a particular denomination, the supervisor then enters the maximum balance to maintain in the safe for that particular denomination, as shown at **205**, followed by the maximum number of tubes to be vended at one time for that denomination as shown at **206**. If a cashier must prepay enough currency to cover a change vend for the particular denomination, this option is selected at block **207**. ("Prepayment" means the cashier must transfer at least enough currency from the cash drawer to a drop safe or other depository at the store and connected to the change safe as mentioned above, before the change safe can accept a request to vend change of the particular denomination.

The supervisor also may select certain denominations for use as a cash payout, as shown at **208**. This means the money in a column containing that denomination may be vended to pay for C.O.D. purchases at a store containing the change safe, for customer refunds, payout of winning lottery tickets, and so on. Typically, supervisory approval would be required for such payouts.

Any denomination can be selected for vending only with supervisory approval, i.e., by entering a supervisor's PIN. This designation is shown at block **209** and usually applies to denominations having a relatively high tube value.

The supervisor may also enter the amount of time, if any, which must elapse after vending a particular denomination, before another vend of this denomination may be made. Selecting the delay feature, and entering the amount of time which must elapse, are shown at block **210** in FIG. **13**.

Lastly, for each denomination the supervisor may restrict the time during which this denomination may be vended. This restriction, shown at **211**, allows entering the time of day at which the change safe can vend the specified denomination, and the time of day after which the change safe cannot vend that denomination. This step, as well as the other steps indicated from **197** through **211**, is selected for each denomination to be vended for a particular change safe, and a supervisor may later change those settings for any denomination of the change safe.

Delivering change to the change safe is now described with reference to FIG. **14**. In a typical application, change is delivered by an armored-car messenger either at designated dates and times as described below, or in conjunction with scheduled content removal from a drop safe at the same location as the change is safe. A typical change delivery contains a predetermined value of preselected denominations, packaged for placement in the tubes **102** for loading into the columns of the change safe as previously described. The delivery messenger places the change delivery in the lower compartment **34** of the change safe, which is the only part of the change safe accessible to the messenger. To access the lower compartment, the messenger carries an electronic touch key compatible with the key port **43** and programmed with information and the messenger's PIN, required for unlocking the door to the lower compartment, to initiate access as shown at **216** in FIG. **14**. The change delivery is in a bag or other container sealed with a numbered bag seal. The messenger is prompted at **217** to enter the number of the seal, and the amount of the change delivery as shown at **218**, into the terminal **41**. The microprocessor then activates the lower door solenoid **72** as indicated at step **219**, allowing the messenger to unlock and open the lower door by turning the knob **35**. The messenger places the change into the lower compartment **34** as indicated at **220**, and then closes and rebolts the lower door. The lower door switch **64** verifies that closure, and the spring-loaded plunger of the lower door solenoid **72** relocks the bolt assembly of the lower door. The switch **74** associated with the lower-door solenoid confirms that the lower door solenoid has indeed secured the locking mechanism to prevent unauthorized reopening of that door. The terminal **41** then displays a delivery message for verification by the messenger, as indicated at **224** in FIG. **14**. After the messenger makes a verifying entry, the printer **42** prints a confirmation of the delivery.

After the messenger has delivered a supply of change to the lower compartment of the change safe, a supervisor can remove that delivery either for loading the change-holding tubes into the columns of the change safe, or adding part or all of the delivered change to the reserve amount stored on the shelves in the upper compartment **78** of the change safe. These operations as discussed with reference to FIG. **15**. After entering a supervisory PIN number at step **228** and selecting the appropriate entry on the terminal **41** to remove the change delivery from the lower compartment, the microprocessor again unlocks the lower door and the supervisor can remove the change delivery from the lower compartment. The supervisor is then prompted to close and rebolt the lower door as at **229**, whereupon the lower door is relocked as mentioned above. The supervisor then may choose to load tubes from the delivery into the columns, as shown by the decision block **230**. By responding "yes", the microprocessor actuates the tube blocker solenoid **140** to unlock the tube blocker **138**, as indicated at **232** in FIG. **15**. The supervisor then actuates the handle **29** (FIG. **1**) to slide the tube blocker to the position where the ports **138***a* align with the ports **28**, permitting access to the upper ends of the columns **83**. The desired amount of change then is loaded into columns of the change safe by inserting the appropriate tubes into the ports **28** in the upper door of the safe; each port preferably is labeled with the denomination previously selected for that port. The tubes drop within the respective columns, and the tubes in each column (excepting the lowermost tubes) are sensed by the array of photosensors **115** associated with that column. This information is used in reporting the contents of a particular column, as discussed below.

After the columns are loaded with tubes, the operator moves the handle **29** to close the tube blocker, as indicated at **236** on FIG. **15**. The tube blocker switch **142** senses that closure, causing operation of the tube blocker solenoid **140** to lock the tube blocker closed so as to prevent tampering with the columns of the change safe. The terminal **41** now displays the amount of change initially delivered to the safe by the messenger, the amount the supervisor transferred to the columns, and the balance if less than all the delivered change was loaded into the columns. This display is indicated at **232**, prompting the operator to select one of the options shown at **233**. The first option allows loading more tubes into columns of the change safe, if any column is not already full. Another option allows adding the balance of change to the reserve location within the change safe. A third option is to apply the 33 unused balance to delivery adjustments, which will subsequently print out on the end-of-day report prepared by the change safe or by a drop safe operatively associated with the change safe.

The secure area within the upper compartment **78** behind the upper door **26**, is called the reserve area of the change safe. This reserve area has one or more shelves on which change may be stored before being loaded into the tubes. Only a supervisor's PIN can open the upper door **26** to access this area. The particular amount of change transferred to the reserve area to await loading into the columns is accounted for by the change safe and is reported as discussed below.

If the supervisor decides to add change to the reserve, the terminal **41** prompts entry of the amounts for each denomination being added to the reserve, as shown at **235** in FIG. **15**. When the supervisor completes those entries, the microprocessor operates the upper door solenoid **57** and prompts the user to open the upper door as indicated at **236**. The amount of change previously entered into the terminal then is placed into the reserve location in the upper compartment **78** of the change safe, after which the supervisor closes the upper door as indicated at **238**. Closure of the upper door is detected by the upper door switch **49**, causing the upper door solenoid to return to the locked position as verified by the upper door solenoid switch **59**. The terminal **41** produces a reminder to the operator if the upper door is not closed and locked. The terminal **41** then produces the display **239** indicating the amount transferred to the reserve, the reserve balances, and gives the operator another opportunity to load tubes into the columns as indicated at **240**. An affirmative answer causes the change safe to unlock the tube blocker door, allowing the operator to repeat the tube loading operation.

Returning to the decision blocks **230** and **231**, the operator upon removing a change delivery from the lower compartment **77** may bypass loading any change into the columns at that time. Instead, the operator may apply the entire amount to the reserve, or to a delivery adjustment, as indicated at **231**. Adding that entire amount to the reserve bypasses the tube-loading steps previously described, and instead presents the operator with the instructions as at **235** to enter the amounts by denomination being added to the reserve in the upper compartment **78** of the change safe.

A supervisory operator can transfer change from the upper reserve to one or more columns of the change safe. This transfer is described with reference to FIG. **16**. The supervisor initiates that transfer by the appropriate menu selection on the terminal **41** and enters a supervisory PIN when prompted. The microprocessor then actuates the upper door solenoid **57**, whereupon the supervisor can unlock and open the upper door to remove change in a desired amount from the shelf in the upper reserve. The operator must then close and relock the upper door, and that condition enables the tube blocker solenoid **140** and prompts the operator to open the tube blocker as shown at **248** at FIG. **16**. The operator then loads the withdrawn change tubes into the columns of the safe, followed by closing the tube blocker door when transfer is completed, as shown at **250**. The terminal **41** then produces a display as shown at **251**, indicating the amount of money in the reserve location before the transfer, the amount transferred into the columns of the change safe (determined by sensing the tubes dropped into each column and from the predetermined value for each tube), and the amount of any remaining reserve balance. The transfer process is now complete, and control of the change safe is returned to the cashier.

A typical vending operation for the change safe is illustrated at **255** with respect to FIG. **17**. The cashier selects the appropriate entry from the main menu and is prompted to enter his or her PIN into the terminal **41** as indicated at **256**. The terminal then presents the cashier with options to vend change of any denomination previously defined for the particular change safe. For example, to vend two rolls of pennies, one roll of nickels, and one roll of dimes, the cashier would twice press the key designated for pennies, then press the key for nickels, and then press the key for dimes. These steps are indicated at **257**, **257*a***, and **257*b***. After entering the correct information, the cashier then presses an appropriate key to commence the vend process. However, before vending commences, the microprocessor compares the cashier's request with the attributes previously entered into the change safe for the various denominations chosen for that safe. For example, if the cashier requested a denomination of change during a time of day restricted for that denomination, or requested a denomination vendable only to a supervisor, the terminal **41** displays an appropriate error message as indicated at **259**. The cashier then presses a key to clear the previous entries and reenters a new request for change. Alternatively, a cashier can terminate the vending operation and seek assistance from a supervisor, whose PIN will permit the appropriate operation.

Once the requested vend is approved, microprocessor **40** operates the ejector subassembly **85** to perform the requested vend. In the example given, the carriage **146** must be positioned beneath a column previously designated for pennies and presently containing at least one tube of that denomination. The sensor array **185** signals the position of the carriage **146** at the start of the requested vend. If the carriage is not positioned beneath a column containing pennies, the microprocessor **40** signals the carriage position motor **150** to turn the lead screw **147** in the direction required to traverse the carriage to a pennies column holding at least one tube of pennies. The carriage position motor **150** stops when the sensor array **185** indicates the carriage has arrived beneath a pennies column. The microprocessor then operates the ejector motor **171**, causing the extractor arm **155** to travel along a complete cycle of movement as previously described, so that the extractor finger **155** engages and rearwardly displaces the tube in the lowermost position of a pennies column. That tube trips the ejector flap **178** and then falls downwardly along the plate **90** to land on the inner end **98** of the ejection chute, from which the tube rolls forwardly to the outer end of the chute **38** for access by the cashier.

The vertical arrays of sensors **115** for each column **83** respond to tubes loaded into the columns at each position except the lowermost position. It is thus possible that a selected vend from a particular column may cause the extractor **154** to cycle through a complete movement path and return to the home position, as detected by the sensor **177**, without actually vending anything. However, that absence of a requested vend will be detected by the absence of a signal from the sensor **181** associated with the tube ejection flap **178**. Accordingly, if the extractor traverses a complete movement path without vending a tube from a particular column, the microprocessor will traverse the carriage **146** to another available column, if any, for the selected denomination. If no such column presently exists, the terminal **41** indicates the failure of that particular vending operation.

The foregoing mechanical steps of vending are repeated until the change safe completes the vend operations previously requested by and authorized to the cashier. For the requested two tubes of pennies, the carriage remains stationary while the extractor **154** again traverses its predetermined path, ejecting a second tube from the pennies column beneath which the carriage is positioned. When the extractor

returns to the home position, the carriage then traverses to a tube containing nickels, and the vending operation is repeated to extract the lowermost tube in that column. The vend operation is complete when the last tube of change requested by the cashier is vended by the change safe.

The audit function **266** performs a partial or complete audit for the contents of the change safe. A complete audit consists of checking the money in the tubes loaded into the delivery columns, and in the lower compartment and the upper reserve area of the change safe. This process is started by choosing the audit function as outlined in FIG. **18**. That function is selected from the appropriate menu at the terminal **41** and requires entering a supervisor PIN. The operator then is prompted as at **267** to state whether or not to audit the tube columns. An affirmative answer unlocks the tube blocker door and prompts the operator at **268** to open that door. The change safe then asks the operator in turn whether to audit each denomination set for that safe, as indicated at **269**. For example, if the operator wants to audit pennies, the microprocessor commands the change dispensing assembly to vend all tubes in the pennies column(s). The operator then removes those vended tubes, enters the currency amount of the pennies thus vended, and then reloads the pennies tubes into the corresponding column(s) of the change safe, as indicated at **272**. The same sequence continues as shown at **273** for the rest of the denominations in the safe, until all columns have been audited or an audit refused for those columns. When this process is complete, the operator is prompted as at **274** to close the blocker door.

The change safe then asks the operator whether to audit the change contained in the upper reserve, as shown at the step **275**. A negative answer causes the microprocessor to print a report as described below, detailing the results of the audit for the tube columns.

If the operator requests auditing the reserve, the microprocessor unlocks the upper door to the safe and prompts the operator to open that door as at **277**. The operator then removes the change in the reserve, and enters the amount of that change by denomination into the terminal **41**. After completing that entry, the operator replaces that change into the reserve as shown as **280** and recloses the upper door. That closure causes the microprocessor to deliver a message asking whether to audit any change delivery remaining in the lower compartment **34** of the safe, as at **277**. A negative answer prompts the microprocessor to print a report of the reserve audit and tube-column audit. An affirmative answer results in unlocking the lower door as at **278**, and prompting the operator to remove any change delivery in the lower compartment. The operator then is asked to enter the amount of each denomination in that delivery, and then replace that change into the delivery bag and return it to the lower compartment, after which the operator is prompted to close the lower door as at **283**. That closure initiates printing a report on the complete audit of the change safe.

A typical printed report **284** for an audit is shown below:

Column	Denomination	Tube Value	Level	Column Value
1	Pennies	.50	9	4.50
2	Nickels	2.00	10	20.00
3	Dimes	5.00	10	50.00
4	Quarters	10.00	10	100.00
5	Ones	20.00	10	200.00
6	Fives	20.00	10	200.00
7	Tens	50.00	10	500.00
8	Twenties	100.00	10	1,000.00
9	Fifties	100.00	10	1,000.00
10	Hundreds	100.00	10	1,000.00
Tube Contents Value				4,074.50
Reserve				655.00
Change Delivered				2,510.00
Change Safe Total Value				7,229.50

The present change safe produces various reports on demand, as indicated by the function **290** in FIG. **12**, in addition to reports as part of specific functions such as auditing the contents of the safe. FIG. **19** outlines typical reporting functions for the change safe, and these functions usually are supervisory and thus require entering a supervisor's PIN in the terminal **41**.

The operator can obtain a quick display of the number of tubes in each column, or a printed report showing those tube levels, as indicated at **291** in FIG. **19**. By selecting tube levels, the terminal produces a display beginning with the first column (X), showing the number of tubes (Y), the denomination (Denom.) for that tube, and the amount of money in that column, all as indicated at **292**. Thus, the first column (usually pennies) might read:

Column One Level is 5, Tubes of Pennies, Value: $2.50.

Each column configured for a particular denomination is displayed in order, and then the total value of all tubes in the columns is displayed as indicated at **293**. The display then shows the total amount in the reserve part of the safe, as at **294**, followed by the amount of any change delivery for the lower compartment as shown at **295**. The total amount in the column and the reserve is then displayed as at **296**.

If the operator instead selects a printed copy of the tube levels, the printer produces a report of the column levels and other information as noted at **292–296**.That printed report may resemble the audit report reproduced above, but it should be understood that the present report or display of column levels is based on information from the sensor arrays associated with the columns; the change safe in producing the present report does not vend all tubes from the columns and then require reloading of those tubes as when performing an audit of the safe contents.

The operator also can request a report as at **300** showing actual usage of the funds in the safe, or as at **301** showing average usage of those funds. These reports are printed for all denominations configured to the change safe, showing the usage of each denomination for each day of the week. Reports on actual usage preferably are prepared for the seven days last preceding the date of the requested report, while average-usage reports show average usage of each denomination per day, averaged over a predetermined number of weeks last preceding the requested report.

The change safe is also programmed to print reports of change vended during each operating shift of the safe location, as indicated at **304**, and for each business day of the store as indicated at **305**. A "business day" for a particular store may not coincide with a calendar day, depending on accounting practices for that store. The reports of change usage by shift and by day are sorted by the cashiers requesting the vends and the denominations vended to each cashier during the time covered by the report.

The supervisor may print a report showing the complete configuration details presently set for the denominations and

columns of the change safe. This activity is shown at **310** in FIG. **19**. A configuration report lists each denomination configured for the particular change safe, the values and tube values set for those denominations, and the amount of change on hand for each denomination. Moreover, the configuration report indicates the parameters previously set for each denomination, such as the parameters identified above with respect to FIG. **15**. A typical configuration report also indicates, by column, the denomination set for each column, and any unused columns presently not configured for a particular denomination. Lastly, the configuration report identifies the schedule of delivery days set for the particular change safe, listed by day of delivery, an earlier day by which change for that delivery must be ordered, and the cutoff time of day for placing that change order.

Ordering supplies of change for the change safe is an operation detailed at **320** on FIG. **20**. The dates and times for change delivery in a typical installation are performed by an armored-car messenger service in accordance with the store supervisor. Knowing those delivery dates and the earlier order-by dates, the supervisor can manually request deliveries of change as indicated at **322**, for the next scheduled delivery to that store. As an alternative to manual ordering based on the supervisor's personal estimate of change needs for the day of delivery and the following days until the next scheduled delivery, the change safe can predict the change needs based on historical change usage by day for the particular safe. This predictive ordering is indicated at **325** in FIG. **20**. With the delivery days already set as indicated at **326**, the microprocessor **40** is programmed to remember the amount of change vended for each denomination, by day, for a predetermined number of weeks in a rolling window of time immediately preceding the present date. The microprocessor calculates average change vends for each denomination per day during that window of time. Based on those average change requirements for each denomination, the known date for the next scheduled delivery of change, and the days between that delivery and the next subsequent scheduled delivery, the microprocessor sums the average usages on those days, for each denomination, and prepares a report of the predicted requirements for the next change delivery. This step is shown at **328** in FIG. **18**. The supervisor may then order the amount of change predicted by the change safe as indicated at **330**, or may vary that order based on other factors such as anticipated abnormal change requirements for a major holiday occurring between the next two scheduled deliveries of change.

It should be understood that the foregoing relates only to a preferred embodiment of the present invention, and that numerous changes and modifications thereto may be made without departing from the spirit and scope of the present invention as defined in the following claims.

What is claimed is:

1. Apparatus for vending articles of predetermined size, the apparatus comprising:

plural adjacent article-receiving columns each having a certain orientation and configured to accommodate plural articles so that each article placed in a column occupies a predetermined location in the column;

means selectably operative to vend an article from a selected column by removing the article from a terminal location within the column, whereupon other articles remaining in the column will shift locations within the column; and

sensors operatively associated with a plurality of the locations in the columns to detect the presence of an article at each such location, so that articles occupying each location of said plurality of locations in each column are detected by the sensors associated with such locations in the columns.

2. Apparatus as in claim **1**, wherein the columns have a vertical orientation, and the terminal location is the lowermost location within the column.

3. Apparatus as in claim **2**, further comprising:

a loading port at an end of the width of each column for inserting elongate articles endwise into the column in a substantially horizontal attitude and on an axis coincident parallel to the longitudinal extent of the article, whereupon each introduced article drops to a lower location not occupied by an article in that column; and

means associated with the end of the column and operative to prevent the elongate articles from dropping in the column until the article is substantially entirely introduced through the loading port into the column, so as to prevent the article from dropping headfirst in the column.

4. Apparatus as in claim **3**, wherein:

the means associated with the loading port comprises a structure having a first portion displaced by an article being introduced through the port and a second portion moveable in response to such displacement to prevent the article being introduced from dropping into the column; and

the second portion moveable in response to substantially complete entry of the article to the upper end of the column to allow the article to drop within the column.

5. Apparatus as in claim **4**, wherein the second portion of the structure moves to block the upper end of the column in the second position so as to support the article being introduced from the loading port; and

the second portion is moveable to unblock the upper end in response to introduction of the article past the loading port.

6. Apparatus as in claim **1**, wherein:

the sensors associated with the columns comprises a sensor associated with each location of the column except the terminal location and responsive to the presence of an article at said each location; and

the vending means is selectably operative to determine whether an article occupies the terminal location of a selected column without regard to whether an article occupies another location in the selected column.

7. Apparatus as in claim **6**, further comprising:

structure associated with each column to permit withdrawing a terminal article from the terminal location only in a first direction;

the vending means comprises a displacement element selectably moveable in a first direction, to displace the terminal article in the first direction so as to vend the terminal article from the column; and

the vending means is selectably operative to move the displacement element on a predetermined path to urge the terminal article in a direction blocked by the structure and to produce a signal in response to failure of the displacement element to move on the predetermined path, whereby the signal from the vending means indicates the presence of an article in the terminal location in the column.

8. Apparatus as in claim **1**, wherein the vending means comprises:

a carriage moveable to a vending location in relation to each column and including a displacement element

selectably operative to remove the article at the terminal location of a selected column, whereby the article is vended from the apparatus; and

sensors responsive to the location of the carriage in relation to the columns.

9. Apparatus as in claim **8**, wherein:

the displacement element is moveable on an orbital path that includes the terminal location in the selected column, so that the displacement element engages and withdraws an article at the terminal location.

10. Apparatus as in claim **9** wherein:

the displacement element is selectably operative to move either in a first direction or in a second direction along the orbital path so as to engage and urge the terminal article; and further comprising

means operative to permit withdrawing the terminal article from the selected column only when the displacement element urges the terminal article in the first direction, and to prevent withdrawal of the terminal article when the displacement element urges the terminal article in the second direction so that the displacement element can traverse the orbital path in the second direction only when an article is not in the terminal location; and

means responsive to a blocked selected movement of the displacement element in the second direction to produce an indication that the terminal location contains an article.

11. Apparatus for vending articles of predetermined size, the apparatus comprising:

plural adjacent article-receiving columns each having a certain orientation and configured to accommodate an article so that each article placed in a column occupies a predetermined location in the column;

means selectably operative to vend an article from a selected column by removing the article from a terminal location within the column, whereupon other articles remaining in the column will shift locations within the column;

means operatively associated with each predetermined location in the columns to detect the presence of an article at each such location, so that the number of articles in each column is detected by the means associated with the columns;

means operatively associated with the apparatus for receiving and storing signals corresponding to a number of different kinds of articles for vending by the apparatus;

the last-mentioned means also receiving and storing signals corresponding to parameters corresponding to each kind of article; and

means operatively associated with the apparatus for receiving and storing signals identifying a particular one of the kinds for storage and vending in selected columns.

12. Apparatus as in claim **11**, wherein the different kinds of articles comprise different denominations of money, the parameters correspond to each denomination, and the identifying signals identify a particular said denomination for storage and vending in each column.

13. Apparatus for vending articles of predetermined size, the apparatus comprising:

plural adjacent article-receiving columns each having a certain orientation and configured to accommodate an article so that each article placed in a column occupies a predetermined location in the column;

means selectably operative to vend an article from a selected column by removing the article from a terminal location within the column, whereupon other articles remaining in the column will shift locations within the column;

means operatively associated with each predetermined location in the columns to detect the presence of an article at each such location, so that the number of articles in each column is detected by the means associated with the columns;

means responsive to the number of articles in the column to determine the number of articles vended over a predetermined amount of time past;

means operatively associated with the apparatus for entering a future date of a next delivery of articles to the apparatus; and

means responsive to the number of the articles vended in a certain unit of time during the predetermined amount of time and responsive to the units of time remaining until the future date, and operative to produce a predicted number of the articles required for the next delivery based on the past vending.

14. Apparatus as in claim **13**, wherein the different kinds of articles comprise different denominations of money received in and vended from the columns, the units of time comprise at least one day, and the predetermined amount of time comprises a plural number of days; and

the means responsive to the number of articles is operative to determine the average daily number of money vends for each denomination, and to produce a predicted amount of money needed for each denomination for the next delivery.

15. Apparatus for vending articles of predetermined size, the apparatus comprising:

plural adjacent article-receiving columns each having a certain orientation and configured to accommodate an article so that each article placed in a column occupies a predetermined location in the column;

means selectably operative to vend an article from a selected column by removing the article from a terminal location within the column, whereupon other articles remaining in the column will shift locations within the column;

means operatively associated with each predetermined location in the columns to detect the presence of an article at each such location, so that the number of articles in each column is detected by the means associated with the columns;

means operatively associated with the apparatus for auditing the contents of selected articles in at least some of the columns by commanding the vending means to vend all selected articles from the one or more columns containing the selected articles;

means for producing signals corresponding to the number of selected articles vended; and

means for producing a report of the audit, showing the number and description of articles vended from each column during the audit.

16. Apparatus for vending articles of predetermined size and substantially tubular shape, the apparatus comprising:

a plurality of adjacent article-receiving columns each having a vertical orientation;

each column having a width perpendicular to the vertical orientation and configured to accommodate the tubular articles, so that articles placed in a column occupy predetermined locations in the column;

means selectably operative to vend an article from a selected column by removing the article from a lower location within the column, whereupon other articles remaining in the column will shift locations within the column;

a loading port at an end of the width of each column for introducing tubular articles into the column in a substantially horizontal attitude and on an axis coincident to the longitudinal axis of the article, whereupon each introduced article falls in the column to a lower location not occupied by an article in that column; and

means associated with the end of the column adjacent the loading port and operative in response to the introduction of the article to support the article until the article is substantially entirely introduced into the column, whereupon the means releases the article to fall in a substantially horizontal orientation within the column.

17. Apparatus as in claim **16**, wherein:

the means associated with the end of the column comprises a structure having a first portion positioned for displacement by one end of the tubular article being introduced to the end of the column through the port, and a second portion moveable in response to such displacement to support the article being introduced, thereby preventing the article from falling into the column; and

the second portion is operable in response to substantially complete entry of the article to the width of the column to allow the article to fall within the column.

18. Apparatus as in claim **17**, wherein;

an edge of the loading port is located in relation to the first portion so as to contact the tubular article as the article is introduced through the loading port to move the second portion to support the article, thereby keeping the first portion displaced with the second portion in position to support the article until the article is substantially fully introduced through the loading port; and

the edge is positioned so that a trailing end of the article moves past said edge as the article is substantially completely inserted through the loading port, whereby the second portion can return to a position allowing the article to fall within the column.

* * * * *